



Strip-TecTM wire granulator

(800) 426-4126

- All American Components
- Proprietary Hardened Tool Steel Blades
- Emergency Stops & Limit Switches
- Fully Stocked Parts House
- No Compressed Air Required
- Dry Separation Unit
- 24 volts Sealed NEMA Control Panel
- Simple to Clean & Maintain
- Large Powerful Cyclone for Max Separation
- Forklift Pockets for easy transportation
- Digital AMP/Load Meter for Efficient Operation
- Dust & Emissions Collector Compliant in all 50 States
- 6 Month Warranty on Material & Workmanship
- 12 Month Warranty on all Electronics

S.T.I. Model	300	400	600
Throughput	350 lbs/hr	475 lbs/hr	875 lbs/hr
Throughput with Shredder	Increase by 25% - 50%	Increase by 25% - 50%	Increase by 25% - 50%
Power Requirements	220V or 440V 70AMP 35AMP	220V or 440V 100AMP 50AMP	220V or 440V 150AMP 75AMP
Rotor Blades	3 rotating, 2 fixed	3 rotating, 2 fixed	3 rotating, 2 fixed

Strip Technology, Inc.

3700 N. Commerce St. Fort Worth, Texas 76106
 Toll Free: 800.426.4126 Local: 817.626.1504 Fax: 817.625.2207
 Email: info@striptec.com Web site: www.striptec.com

Strip-Tec™ wire granulator

(800) 426-4126



300/400



600



 **MADE IN AMERICA** 

Striptec Model	Length	Width	Height	Weight	Mill H. P.	Complete H. P.
300	7 Ft.	5 Ft.	8 ½ Ft.	4,750 Lbs.	20	30
400	7 Ft.	5 Ft.	8 ½ Ft.	5,000 Lbs.	30	40
600	10 Ft.	8 Ft.	8 ½ Ft.	7,500 Lbs.	40	60

•Increase your production with a shredder and infeed conveyor

Strip Technology, Inc.

3700 N. Commerce St. Fort Worth, Texas 76106

Toll Free: 800.426.4126 Local: 817.626.1504 Fax: 817.625.2207

Email: info@striptec.com Web site: www.striptec.com